

## Automated, water-free vial thawing systems


SAFE THAWING FOR CRYOPRESERVED BIOLOGIC MATERIALS




ThawSTAR® Automated Thawing Systems were designed to provide a water-free, uniform, and reproducible warming profile for frozen biologics suspended in various primary containers. The ThawSTAR technology provides sensor-based thawing algorithms designed to deliver consistent thawing outcomes.

## **ADVANCED THAWING VALUE:**

- Automation and standardization ThawSTAR products ensure consistent thawing results with reproducible algorithms designed to eliminate manual processing.
- Reduced contamination exposure ThawSTAR solutions are 100% water-free, eliminating sample contamination risks often associated with water baths and other thawing systems.
- Programmed precision For optimizable ThawSTAR models, thawing algorithms may be customized to the specific container and biologic. Qualified BioLife technicians will tailor the program to maximize thaw outcome.
- Qualifiable ThawSTAR Systems are qualifiable and can be scaled into end point of use facilities.












Figure 1: Cell viability (left panel) and recovery (right panel) of PBMC were measured using trypan blue exclusion on a hemacytometer. Recovery is the number of viable cells post-thaw as a percentage of the pre-freeze viable cells. No statistical difference in viability (2-way ANOVA with post hoc Sidak test) or recovery (unpaired two-tailed t-test) at p < 0.05 were found. Data courtesy of Dr. Mars Stone at the Blood Systems Research Institute.



## Available in various models to support R&D, commercial manufacture, and end point of use.

















Product Family	ThawSTAR® CFT		ThawSTAR® CSV		ThawSTAR® AT			
Product Name	ThawSTAR CFT1.5	ThawSTAR CFT2	ThawSTAR CSV2	ThawSTAR CSV5	ThawSTAR AT1	ThawSTAR AT2	ThawSTAR AT6	ThawSTAR AT10
Compatible Vials	1.5 mL cryogenic vials	1.8 mL to 2.0 mL cryogenic vials	2.0 mL CellSeal® Vials	5.0 mL CellSeal® Vials	1.0 mL Aseptic Technologies Closed Vials®	2.0 mL Aseptic Technologies Closed Vials®	6.0 mL Aseptic Technologies Closed Vials®	10 mL Aseptic Technologies Closed Vials®
Recommended Fill Volume	0.8 – 1.5 mL	1.0 – 2.0 mL	1.0 – 2.0 mL	2.5 – 5.0 mL	1.0 mL	0.5 – 2.0 mL	2.0 – 5.0 mL	4.0 – 8.0 mL
Thaw Time	<3 mins	<3 mins	<3 mins	<3 mins	3 - 8 mins, varies by vial size			
Dimensions (Diameter x Height)	11.0 x 14.5 cm (4.3 x 5.7 in)	11.0 x 14.5 cm (4.3 x 5.7 in)	10.9 x 14.5 cm (4.3 x 5.7 in)	10.9 x 14.5 cm (4.3 x 5.7 in)	11.0 x 14.5 cm (4.3 x 5.7 in)	11.0 x 14.5cm (4.3 x 5.7 in)	11.0 x 14.5 cm (4.3 x 5.7 in)	11.0 x 14.5 cm (4.3 x 5.7 in)
Compliance	CE mark (IEC61326 and IEC61010), RoHS, WEEE							
Voltage	US, EU, UK							
Input/Output Voltage	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A	AC 100 - 240V, 50 - 60 Hz 12V DC, 5.0A
Power Rating	12V DC, 3.0A							



## **Additional ThawSTAR® Transporters**

ThawSTAR Transporters were designed specifically to move ultracold samples from their long-term storage freezers to the thawing system. Comprised of an insulative foam layer and lid with space for dry ice and various samples, ThawSTAR Transporters are an ideal temporary holding solution until all samples have been thawed and processed. Not compatible with ThawSTAR CSV models and CellSeal® Vials.



Contact SalesOne@biolifesolutions.com for more information or to place an order.



3303 Monte Villa Parkway Suite 310 Bothell, WA 98021 USA

T +1.866.424.6543

F +1.425.402.1433

E SalesOne@biolifesolutions.com BioLifeSolutions.com

2024© ThawStar Solutions, a part of BioLife Solutions. All rights reserved.

**Thawing Solutions**